

The same process, four times the plate.

Same chassis, same controls, same slicer as the A50 — with four times the build area for small series and larger parts.

BUILD VOLUME	LASER	LAYER	BLUE LASER
Ø100 × 100 mm	300–1000 W fiber	15–100 µm	445 nm, 250 W

from \$99,000

300 W · 500 W and 1000 W quoted on request



- Four times the build area**
 Ø100 × 100 mm — nesting, small series, and parts an A50 cannot hold.
- A blue laser for reflective metals**
 445 nm, 250 W optional — copper, gold and silver.
- Open where it matters**
 Our own slicer, every parameter exposed, proven sets included.
- Nothing else changes**
 The same chassis and footprint as the A50: 1150 × 730 × 2050 mm.
- A platform that holds 900 °C**
 250 °C as standard, 900 °C optional.
- A qualified process moves here as a file**
 What runs on an A30 or an A50 runs here without being rebuilt.

SIXTEEN ALLOYS PROVEN TO DATE. THE LIST IS NOT CLOSED.

Stainless 316L · 17-4PH

Inconel 625 · 718

Ti-6Al-4V · TiAl

AlSi10Mg · 6061

Cobalt chrome

Tool steels H13 · M300

Copper · CuCrZr

W · Ta · Nb · Mo

Gold · Silver · Platinum

High-entropy alloys

Specifications and what it takes to run one.

527 g of 316L powder to run a set of test parts 10 mm tall.

POWDER TO START A BUILD	316L STEEL	TI-6AL-4V	ALUMINIUM
Test parts, 10 mm tall	527 g	304 g	185 g
A build of 20 mm parts	1.05 kg	608 g	371 g
Dispenser filled to full height	10.53 kg	6.08 kg	3.71 kg
Metal in the part itself — a 10 mm cube	7.9 g	4.5 g	2.7 g

Model	A100-300	A100-500	A100-1000
Technology	Laser powder bed fusion (LPBF)		
Build volume	Ø100 × 100 mm		
Laser	300 W fiber, 1064 nm	500 W fiber, 1064 nm	1000 W fiber, 1064 nm
Laser spot size	75 µm (55 µm optional)		
Optional blue laser	445 nm, 250 W		
Scan system	Galvo scan head + F-theta lens		
Max scanning speed	up to 12 m/s		
Layer thickness	15–100 µm		
Build plate heating	250 °C standard · 900 °C optional		
Inert gas	Argon, < 2 L/min		
Material changeover	3 hours		
Software · file format	AO Build Studio + AO Build Slicer · STL		
Power supply	110 V, 1 phase	220 V, 3 phase	220 V, 3 phase
Power consumption	4 kW	6 kW	8 kW
Dimensions (W × D × H)	1150 × 730 × 2050 mm (45.3 × 28.7 × 80.7 in)		
Weight	350 kg (772 lb)	400 kg (882 lb)	450 kg (992 lb)
Alloys proven to date	16+ — not a fixed list		

What a system comes with

- AO Build Studio and AO Build Slicer, with proven parameter sets for the alloys you order.
- Build plate, powder dispenser, filters, seals and the tools for a material change.
- **Installation and operator training**, with a named engineer on the account.
- **Warranty**: 12 months on laser, scanner, blower, motors and electrical systems.
- **Lead time**: some configurations ship from stock; built to order is 12–16 weeks.

What you will also need

- **Required**: wet vacuum cleaner (explosion-proof for reactive metals) and a sieving machine.
- **Recommended**: heat-treatment furnace, bandsaw or small lathe, polishing tool.
- **Serviceable in your own lab**: filters, seals, hoses and recoater blades are ordinary components you can source locally.

The line it belongs to

A30

Ø30 × 60 mm · 200 or 300 W fiber · 110 V, single phase

from \$59,000

A50

Ø50 × 100 mm · 300–1000 W · blue laser and 900 °C plate optional


from \$89,000

A100

Ø100 × 100 mm · 300–1000 W · blue laser and 900 °C plate optional

from \$99,000

The same slicer, the same controls, the same file. A process developed on one machine transfers to the others without being rebuilt.



Designed and manufactured by Additive Plus in Gardena, California — spares, service and your engineer are all here. Tell us the alloy and the part, and we will say what an A100 does with it.

info@aometal.com · info@additiveplus.com
(747) 800-4854 · aometal.com · additiveplus.com